

# TEMPERATURE CONTROL UNIT

# VT SERIES

Water Unit with LXT Series  
Control Instrument

- **Stainless Steel Cabinetry**
- **LXT Series Control Instrument**
- **Modulating Cooling Valve**
- **Operating Temperatures to 250°F**
- **Heaters to 34 kW and Pumps to 7.5 HP**

The VT Series temperature control unit is the new Old Soldier for temperature control. Designed by skilled and experienced Veteran Engineers that know the industry. This temperature control unit is competent of your needs, built for long term dependable full time operations. For precise temperature control, no other controller beats the VT Series model.



VT-1035-LXT

#### TANK CONSTRUCTION:

- Twin tanks - separate heating and cooling cylinders
- Cast iron material
- Machined process connections
- Flange mounted to pump casing
- Thermoformed cover panel

#### PUMP:

- Cast iron casing - custom design for increased flow
- Bronze pump impeller
- Pump seal flush
- Stainless steel pump motor shaft

#### COOLING VALVE:

- 3/8" modulating valve
- Microprocessor controlled
- Integral to cooling cylinder
- Field serviceable

#### HEATER:

- Flanged bolt-in mount
- Stainless sheath
- Mercury heater contactor

#### CABINERY:

- Stainless steel
- Hinged electrical cabinet door
- Lift-off mechanical cover
- Portable, on casters
- Process pressure gauges

#### LIMIT DEVICES:

- Water supply pressure switch
- Motor overloads
- Pressure relief valve
- High temperature limit
- Fused control circuit

#### ELECTRICAL:

- Process pump motor starter
- Fused transformer
- 10' power cord installed (on models with 1 - 3 HP and 6 - 16 KW)

#### 'LXT' SERIES CONTROLLER:

- Touch screen simplicity
- 4.3" full color touch screen interface
- More than 15 screens with custom set-up, operation & system monitoring information.
- Home screen includes continuous setpoint and to process temperature.
- Digital flow rate display and from process temperature on informational screen.
- % Heating or Cooling indication on home screen.
- Standard shut down pump seal cooling feature.
- User configurable automatic start-up venting.
- Out-of-spec alarm including standard audible signal.
- Pump rotation monitor.
- Selectable SPI or Modbus RTU communication.
- Optional Modbus TCP communication.
- Optional remote panel with interconnecting cable.
- Operates exclusive AVT modulating cooling valve.

#### WARRANTIES:

- 2 year controller
- 2 year cooling valve
- 2 year heater
- 2 year mechanical

**Authorized Dealer**  
**Southgate Process Equipment, Inc.**  
87 Hickory Springs IND. Drive  
Canton, GA 30115  
Ph: (770) 345-0010  
Email: [sales@southgatepe.com](mailto:sales@southgatepe.com)

For best pricing call Southgate Process Equipment @ (770) 345-0010

## Mechanical System



## 'LXT' Control Instrument

Microprocessor instruments control and monitor all aspects of the operation to assure accurate control and dependable operation. The controls are designed to support the specific and unique requirements of process temperature control in an industrial environment.



Touch Screen Display

## Options

- Dual zone dolly with water manifold or with electrical junction box
- Stacking stand with water manifold or with electrical junction box
- Mold purge kit
- Non ferrous tanks
- Bronze pumps and/or piping
- Total non ferrous units
- Closed circuit designs
- Audible alarm
- Visual/audible alarm beacon

[For best pricing call Southgate Process Equipment @ \(770\) 345-0010](http://www.southgatepe.com)

# TEMPTEK

87 Hickory Springs IND. Drive Canton, GA 30115 Ph: (770) 345-0010 Website: [www.Southgatepe.com](http://www.Southgatepe.com) Email: [sales@southgatepe.com](mailto:sales@southgatepe.com)

Since product innovation and improvement is our constant goal, all features and specifications are subject to change without notice. #ADV-941 updated 11/11/2015 ©2015 TEMPTTEK, INC.

# Specifications

Model	Heater	Process Pump			Full Load Amperage @ 3Ø / 60hz <sup>2</sup>		Dimensions			Process Connections		Shipping Weight
	kw <sup>1</sup>	HP	GPM	PSI	230	460	Height	Width	Depth	To & From Process	Supply & Drain	LBS <sup>3</sup>
VT-150	6	½	20	30	17.0	8.5	28¼	12½	19½	1¼	½	195
VT-175	6	¾	35	30	17.8	8.9	28¼	12½	19½	1¼	½	200
VT-1100	6	1	45	30	18.6	9.3	28¼	12½	19½	1¼	½	205
VT-1150	6	1½	62	30	20.2	10.	28¼	12½	19½	1¼	½	205
VT-1200	6	2	75	30	21.8	10.9	28¼	12½	19½	1¼	½	210
VT-1300	6	3	80	30	24.6	12.3	28¼	12½	19½	1¼	½	220
VT-275	10	¾	35	30	27.8	13.9	28¼	12½	19½	1¼	½	200
VT-2100	10	1	45	30	28.6	14.3	28¼	12½	19½	1¼	½	208
VT-2150	10	1½	62	30	30.2	15.1	28¼	12½	19½	1¼	½	208
VT-2200	10	2	75	30	31.8	15.9	28¼	12½	19½	1¼	½	213
VT-2300	10	3	80	30	34.6	17.3	28¼	12½	19½	1¼	½	223
VT-2500	10	5	90	34	40.3	20.2	44	16	24	2	½	275
VT-2750	10	7½	100	47	47.1	23.5	44	16	24	2	½	290
VT-375	16	¾	35	30	42.8	21.4	28¼	12½	19½	1¼	½	205
VT-3100	16	1	45	30	43.6	21.8	28¼	12½	19½	1¼	½	210
VT-3150	16	1½	62	30	45.2	22.6	28¼	12½	19½	1¼	½	210
VT-3200	16	2	75	30	46.8	23.4	28¼	12½	19½	1¼	½	220
VT-3300	16	3	80	30	49.6	24.8	28¼	12½	19½	1¼	½	225
VT-3500	16	5	90	34	55.4	27.7	44	16	24	2	½	285
VT-3750	16	7½	100	47	62.2	31.1	44	16	24	2	½	300
VT-475	24	¾	35	30	63.1	31/6	44	16	24	1¼	½	270
VT-4100	24	1	45	30	63.9	32.0	44	16	24	1¼	½	275
VT-4150	24	1½	62	30	65.5	32.8	44	16	24	1¼	½	280
VT-4200	24	2	75	30	67.1	33.6	44	16	24	1¼	½	285
VT-4300	24	3	80	30	69.9	35.0	44	16	24	1¼	½	290
VT-4500	24	5	90	34	75.5	37.8	44	16	24	2	½	295
VT-4750	24	7½	100	47	82.3	41.2	44	16	24	2	½	310
VT-575	34	¾	35	30	88.2	44.1	44	16	24	1¼	½	280
VT-5100	34	1	45	30	89.0	44.5	44	16	24	1¼	½	285
VT-5150	34	1½	62	30	90.6	45.3	44	16	24	1¼	½	290
VT-5200	34	2	75	30	92.2	46.1	44	16	24	1¼	½	295
VT-5300	34	3	80	30	95.0	47.5	44	16	24	1¼	½	300
VT-5500	34	5	90	34	100.6	50.3	44	16	24	2	½	305
VT-5750	34	7½	100	47	107.4	53.7	44	16	24	2	½	320

Notes: 1. Derate heater output by 25% for 208/3/60 operation. 2. Consult factory for 50hz operations. 3. Approximate unit shipping weight. <sup>1</sup>

